

TRUE TECHNOLOGY		
Woodpecker Cottage, Red Lane, Aldermaston, Berks, RG7 4PA		
Tel: 01189-700-777 Web: trutek-uk.com E-mail: sales@trutek-uk.com		
Price list December 2008		
CODE	DESCRIPTION	UK LIST GBP
	SupaSlim filter wheel for use with 1.25" and 48mm disk, motorised, inc onboard electronics, psu, RJ cable + PC adapter,s/w, carrying case now included as standard	
	SCT thread sideplates standard on all versions unless otherwise specified **	
	** SS-50/50a M54 sideplates standard unless otherwise specified	
	* You can mix'n'match sideplates on all versions as required at no extra cost *	
SS-5	With internal 5 x 48mm/2" disk	475
SS-6d	With internal 6 x 1.25" + dark position disk	475
SS-7	With internal 7 x 1.25" disk	475
SS-8	With internal 8 x 1.25" disk	475
SS-50	Includes FW-50 disk for 50mm unmounted filters, plus 5 'O'-Rings	495
SS-50a	As above, with FW-50a tapped disk, nylons screws/washers, large and small 'O' Rings	499
	The 50a disk is for 50mm diameter glass over 2mm thick (3mm max thickness)	
*****	*****	
	additional disks	
FW-'X' (5,6d,7,8)	eg FW-6d = additional disk assembly with 6d disk, for motorised SS wheel	65
FW-50	Disk for 50mm unmounted glass up to 2mm thick , including standard (large) 'O' Rings	75
FW-50a	As above, but tapped, including nylon screws/washers, large and small 'O' Rings	80
	The 50a disk is for 50mm diameter glass up to 3mm max thickness	
	FW50/FW50a disks only compatible with upgraded or post S/N 500 wheels	
*****	*****	
O-RING-L	Pack of 5 'O'-Rings - large size for use with FW-50 and FW-50a	3
O-RING-S	Pack of 5 'O'-Rings - small size for use with FW-50a only	3
*****	*****	
SS-CASE	Main carrying case with integral handle, foam inserts, 261w x 175d x 77h	18.50
DSK-CASE *	Disk carrying case with integral handle, foam inserts, 220w x 160d x 40h	12.50
	* if ordered at same time as disk	10
*****	*****	
FHU	Field Hand Unit for use with any motorised wheel - note no pc control at the same time	75
*****	*****	
PL-M54	M54 sideplate	20
PL-SCT	SCT sideplate	20
	M54-SCT drop-down adapters, as required, price per adapter ordered with upgrade	10
	M54-SCT drop-down adapters enable use of existing SCT thread adapters	
*****	*****	
RINGSET	Set of 5 blank 1.25" filter rings + lock-rings + extraction tool	25
125RING	Additional blank filter ring + lock-ring	6
*****	*****	
Adapters	Note: standard thread on all wheel faceplates is female SCT thread (2" x 24tpi)	
M54M-SCTF	Drop-down adapter for M54 plate to convert back to standard female SCT thread	15
M54M-M	M54 male-male adapter, mates with camera adapters on Tak scopes	25
M54C	M54 flangeless coupling adapter to camera, with internal M48 filter thread	20
2PFM-M54M	2" push-fit to M54 male-male adapter, inc M48 filter thread in front	20
SCT-T-LR	Long T-thread adapter inc lock-ring, for SXV CCD etc	30
SCT-M42-LR	As above but with M42 x 1.0 'Pentax S' thread for SX 'HX' and 'MX' CCDs, etc	30
SCTM-M-LR	Long SCT-thread, male adapter, inc lock-ring, for large chip CCDs	30
SCTM-2PFF	Short 2" push-fit female barrel, 20mm internal depth, with two thumbscrews	25
SCTM-2PFF-L	Long 2" push-fit female barrel, 38mm internal depth, with two thumbscrews	30
SCTM-TF	Drop-down adapter to T (M42 x 0.75) female thread, 2mm flange	15
SCTM-M42F	Drop-down adapter to 'Pentax' (M42 x 1.0) female thread, 2mm flange	15
SCTM-M48F	Drop-down adapter to M48 x 0.75 female thread, 2mm flange	15
SCT-M54TAK	Converts output to M54 female for use with 'Wide' T-Rings	30
WT-EOS	Wide T-Ring for Canon EOS, use with M54 adapter above	35
WT-NIK	Wide T-Ring for Nikon, use with M54 adapter above	31
WT-M42	Wide T-Ring for M42, use with M54 adapter above	31
2PFM-TM	Low profile adapter for 2" focusers, takes 48mm filter, 20mm barrel length	20
2PFM-SCTM	Low profile adapter for 2" focusers, takes 48mm filter, 20mm barrel length	20

LR-SCT/T/M42	Locking rings, 4.5mm thickness - for SCT, T or M42, eg LR-SCT = SCT thread	15
SCTF-2PFF	Female-female adapter, screws onto SCT back to convert to 2" push-fit	30
T-RING	Standard 'Pentax' T2 mount (M42 x 1.0mm), use with M42 drop-down	5
SCTF-TM	Low profile adapter to convert SCT to T-thread, use with T drop-down	15
TAK72-SCTM	low profile adapter to convert Tak 2.7" focuser to SCT thread, use with LR-SCT	30
317M	male 1.25" push-fit barrel, length 1", use with M42 drop-down	15
T-EXT	T-thread extender tubes, 5,10,20,40mm	55
M42A	Low profile male-male adapter M42-M42, takes 1.25" filter, 4mm flange	15
M42C	As above, T-thread-T-thread, 4mm flange	15
2010RDF	20/10 Auto shut-off red dot finder	29.95
	Prices subject to change	
	Warranty on all items - one year from date of delivery	
	Prices in pounds Sterling	
	VAT included in list price - UK VAT rate 15%	
	Bank IBAN GB88 LOYD 3018 4500 999192	
	BIC LOYDGB21415	